

Cartridge Filter Of SS Housing

不锈钢外壳滤芯过滤器



产品特点

Characteristic

01

不锈钢过滤器壳体采用快开的方式,结构紧凑,节省空间,更换滤芯快捷方便。

Filter housing adopts quick-opening design, compact structure for space saving and easy replacement of cartridges.

03

不锈钢过滤器材质为SS304、SS316、316L。

Filter housing is made of stainless steel 304, 316 or 316L.

02

不锈钢过滤器标准设计压力为87psi (0.6MPa), 其他压力等级可定制。

Filter housing with standard design pressure of 87psi (0.6MPa), which can be customized for other pressure range.

04

耐高压,耐高温,工艺成熟,应用范围广。

High pressure and temperature resistance, mature technology and wide range of applications.

技术参数

Technical Data

产品型号 Model	单元数量 No. Of Cartridges	最大流量 Max. Flow gmp (m ³ /h)	壳体公称 直径 Housing Diameter	壳体材质 Housing Material	进出口连接 方式 Connection
BOC CFVS 1040-1 BOC CFHS 1040-1	1	220 50	10"	SS304/SS316 特殊材质可定制	法兰连接 Flange
BOC CFVS 1640-2 BOC CFHS 1640-2	2	440 100	16"		
BOC CFVS 1840-3 BOC CFHS 1840-3	3	660 150	18"		
BOC CFVS 2040-4 BOC CFHS 2040-4	4	880 200	20"		
BOC CFVS 2240-5 BOC CFHS 2240-5	5	1100 250	22"		
BOC CFVS 2440-6 BOC CFHS 2440-6	6	1320 300	24"		
BOC CFVS 2440-7 BOC CFHS 2440-7	7	1540 350	24"		
BOC CFVS 2640-8 BOC CFHS 2640-8	8	1760 400	26"		
BOC CFVS 3040-9 BOC CFHS 3040-9	9	1980 450	30"		
BOC CFVS 3040-10 BOC CFHS 3040-10	10	2200 500	30"		

*范例/Example (BOC CFVS 1040-1)

CFVS **10** 10 = 过滤器直径10寸
10: Filter housing diameter 10" **40** 40 = 滤芯长度40寸
40: Cartridge length 40" **-1** 1 = 1芯
1: One cartridge